
AUGUSTA UTILITIES DEPARTMENT 2102 HIGHLAND AVENUE WATER TREATMENT PLANT FILTER MODIFICATIONS - PHASE 2




MAYOR GARNETT JOHNSON COMMISSION


JORDAN JOHNSON
STACY PULLIAM
CATHERINE SMITH-RICE
ALVIN MASON
DON CLARK

TONY LEWIS
TINA SLENDAK
BRANDON GARRETT
FRANCINE SCOTT
WAYNE GUILFOYLE

AUGUSTA UTILITIES DEPARTMENT DIRECTOR: WES BYNE, P.E.




- 1. THE CONTRACTOR SHALL REVIEW AND VERIFY THE EXISTING GROUND CONFIGURATIONS AND INFORM HIMSELF OF THE CONDITIONS TO BE ENCOUNTERED DURING CONSTRUCTION.
- 2. THE LOCATIONS OF UTILITIES SHOWN ON THE DRAWINGS HAVE BEEN DETERMINED FROM UTILITY COMPANY/DEPARTMENT RECORDS AND PERSONNEL. THERE MAY BE OTHER UTILITIES NOT SHOWN ON THE DRAWINGS WHICH PRESENTLY EXIST IN THE AREA OF CONSTRUCTION. THE ENGINEER AND/OR OWNER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION SHOWN.
- 3. THE CONTRACTOR SHALL CONTACT ALL UTILITY AGENCIES PRIOR TO COMMENCING CONSTRUCTION FOR PURPOSES OF LOCATING EXISTING UTILITIES ON THE PROJECT SITE. THE CONTRACTOR SHALL COORDINATE AND PROVIDE FOR THE PROTECTION OF CONFLICTING UTILITIES. UTILITIES OR OTHER OBSTRUCTIONS REQUIRING RELOCATION OR FACILITIES DAMAGED DURING THE COURSE OF CONSTRUCTION SHALL BE RELOCATED AND/OR REPAIRED BY THE CONTRACTOR AT NO COST TO THE OWNER.
- 4. THE DRAWINGS CONTAIN DETAILED VERTICAL AND HORIZONTAL CONTROL AND CONTROL POINTS FOR THE LAYOUT OF THE PROJECT. DETAILED CONSTRUCTION STAKING SHALL BE UNDERTAKEN BY THE CONTRACTOR.



PROJECT VICINITY MAP

SCALE: 1" = 200'





SECTION OR ELEVATION MARKER ARROW INDICATES VIEWING ORIENTATION

SECTION LETTER
IDENTIFICATION


SHEETS WHERE THE SECTION OR
ELEVATION IS CUT OR CALLED OUT

SECTION


A SECTION

SO2 SO4 SCALE: 1/4" = 1'-0"

SECTION OR ELEVATION TITLE




	Sheet List Table
Sheet Number	Sheet Title
	GENERAL
G0	COVER SHEET
G01	GENERAL NOTES, VICINITY MAP AND DRAWING INDEX
	STRUCTURAL
S01	FILTERS NO 2 AND NO 8 STRUCTURAL REPAIRS
S02	FILTERS NO 2 AND NO 8 STRUCTURAL DETAILS
	MECHANICAL
M01	EAST FILTER BUILDING FLOOR PLAN
M02	FILTER DEMOLITION PLAN
M03	FILTERS NO 2 & NO 8 DEMOLITION SECTIONS
M04	FILTER NO 2 MODIFICATIONS PLAN
M05	FILTER NO 8 MODIFICATIONS PLAN
M06	FILTER NO 2 SECTIONS
M07	FILTER NO 8 SECTIONS
M08	MISCELLANEOUS DETAILS 1
M09	MISCELLANEOUS DETAILS 2
	INSTRUMENT
IO1	P & ID LEGEND
102	P & ID FILTER NO 2
103	P & ID FILTER NO 8
	ELECTRICAL
E01	ELECTRICAL NOTES
E02	ELECTRICAL SYMBOLS
E03	ELECTRICAL SYMBOLS 2
E04	POWER SINGLELINE
E05	FCC 1-2 CONTROL SINGLELINE
E06	FCC 3-4 & FCC 5-6 CONTROL SINGLELINE
E07	FCC 7-8 & FCC 9-10 CONTROL SINGLELINE
E08	HF PANEL SCHEDULES
E09	LF1 & LF2 PANEL SCHEDULES
E10	LF3 & LF4 PANEL SCHEDULES
E11	LF5 PANEL SCHEDULE
E12	ELECTRICAL FILTER FLOOR PLAN
E13	FILTER 2 ELECTRICAL PLAN
E14	FILTER 8 ELECTRICAL PLAN




MAP							
ENT							
TINDIANT							
	NO.	NO. DATE	REVISION	7	ВУ	APVD	
CE 2	DESIGN	ED BY:	DESIGNED BY: DRAWN BY:	HECKED BY:	APPROVED BY:	BY:	
JL 2		JB	RAM	AB		JD	

GENERAL NOTES, VICINITY AND DRAWING INDEX AUGUSTA UTILITIES DEPARTMENTEND AVE WATER TREATMEN





FILE	SEE LEFT
	VERIFY SCALE
	BAR IS ONE INCH ON ORIGINAL DRAWING
DATE	MARCH 2025
PROJ.	100339.11



- 1/2" SST PLATE

ANCHORS.

SCALE: 1"=1'-0"

| 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7 1/4" | 7

PRIOR TO DEMOLITION WORK INSTALL SST PLATE TO ISOLATE

STAINLESS STEEL PLATE

FILTER FROM INFLUENT CHANNEL. ONCE FILTER IS READY TO BE PLACED BACK IN SERVICE, REMOVE SST PLATE AND EXPANSION

— STRIP TYPE WATERSTOPS

SECTION

(TYP.)

#4 VERT. @ 12" DOWELED

INTO TOP OF WALL (TYP) __

- REMOVE TROUGH

(SEE "M" DWG)

– #4 HORIZ. @ 12" DOWELED

INTO EXISTING WALL EACH END

TNEMEC SYSTEM

CONCRETE REPAIR

REMOVE TROUGH

(SEE "M" DWG)

SUBSTRATE. THE SURFACE SHALL BE CLEAN AND DRY. PRIME ALL EXPOSED REBAR OR OTHER METAL WITH TNEMEC SERIES 1 OMNITHANE PRIMER APPLIED AT 2.5 – 3.5 DRY MILS PRIOR TO THE APPLICATION OF THE CONCRETE REPAIR MORTAR LISTED BELOW.

PATCH & SKIM COAT:


TNEMEC SERIES 218 MORTARCLAD TO FILL AND SMOOTH THE SURFACE OF THE WALL. IF THE DETERIORATION IS GREATER THAN ONE INCH, USE TNEMEC SERIES 217 MORTARCRETE. THE GOAL IS TO SEAL AND PROVIDE A UNIFORM AND SMOOTH SURFACE.

2ND COAT: SERIES N140-1255 POTA-POX PLUS 4.0 – 6.0 3RD COAT: SERIES 21 EPOXOLINE 12.0 - 14.0 **NEDUR**

FILE	SEE LEFT	
	VERIFY SCALE	
	BAR IS ONE INCH ON ORIGINAL DRAWING	


DATE MARCH 2025 PROJ. **100339.11**

S01





NOTES:

- 1. SUPPORT MATERIAL TO MATCH GRATING MATERIAL UNLESS OTHERWISE NOTED.
- 2. PROVIDE GRATING SUPPORTS ALL AROUND OPENING, UNLESS OTHERWISE NOTED.
- 3. GRATING MAY BE CONTINUOUS OVER INTERIOR SUPPORT, UNLESS OTHERWISE NOTED.
- 4. COAT ALL ALUM. GRATING, SEATS, AND SUPPORTS IN CONTACT W/ CONCRETE W/ BITUMINOUS PAINTING SYSTEM.









NOTE: ALL MATERIAL SHALL BE ALUMINUM (U.N.O.)












SECTION









TYPE 2 REPAIR - CONCRETE SPALL





TYPE 3 REPAIR - CONCRETE SPALL





DE


No. SE001314 STRUCTURAL


FILE	SEE LEFT
	VERIFY SCALE
	BAR IS ONE INCH ON ORIGINAL DRAWING
(0 1"
DATE	MARCH 2025
PRO.I	100339 11


S02




















NOTES:


- 1. INSTALLING CONTRACTOR SHALL FURNISH HARDWARE FOR TROUGH INSTALLATION AS REQUIRED BY TROUGH MANUFACTURER.
- 2. INSTALLING CONTRACTOR SHALL FURNISH STABILIZER SUPPORTS & HARDWARE AS REQUIRED BY TROUGH MANUFACTURER.




















- 1. INSULATED PIPING: 2. INTERRUPT INSULATION AT BOTH SIDES OF WALL. INSTALL INSULATION FLUSH WITH WALL AFTER WATER TIGHT INSTALLATION OF MECHANICAL SEAL.
- 3. SEALS FOR PROCESS AIR SHALL BE HEAT RESISTANT.
- 4. WALL OPENING DIAMETER AS REQUIRED FOR PASSING PIPE AND THE MECHANICAL SEAL MANUFACTURER REQUIREMENTS.
- 5. DOUBLE LINK SEAL FOR WALLS 24" THICK AND GREATER





AU(HIGHLAI FIL




FILE SEE LEFT **VERIFY SCALE** BAR IS ONE INCH ON ORIGINAL DRAWING DATE MARCH 2025

PROJ. **100339.11**


M08


DWG.




INSTRUMENTATION BOARD EQUIPMENT SCHEDULE

- 1 INLET PIPE PENETRATION (TYP 3)
- 2 TURBIDITY METER (TYP 2)
- TURBIDITY METER DIGITAL READOUT (TYP 2)
- 4 PARTICLE COUNTER
- 5 RECEPTACLE (TYP 2)
- 6 STAINLESS STEEL DRAIN TROUGH
- 7 PVC DRAIN PIPING ROUTED TO FLOOR DRAIN ADJACENT TO FILTER WALL
- 8 STAINLESS S SUPPORTS STAINLESS STEEL INSTRUMENTATION BOARD







				SLIDE	GATE S	SCHEDU	JLE				
					HEIGHT		WIDTH	MAXIMUI	M HEAD		
GATE ID	TYPE	SERVICE	MOUNT	OPERATION	A (INCHES)	B (INCHES)	C (INCHES)		JNSEATING (FEET)	VOLTAGE	REMARKS
SG-302I	UPWARD OPENING SLIDE GATE	FILTER NO 2 - INFLUENT	FLUSH MOUNT CONCRETE WALL	ОНС	24	30	24	4	4	480	SEE NOTE 1
SG-302D	UPWARD OPENING SLIDE GATE	FILTER NO 2 - DRAIN	FLUSH MOUNT CONCRETE WALL	ОНС	24	72	24	9	9	480	SEE NOTE 1
SG-308I	UPWARD OPENING SLIDE GATE	FILTER NO 8 - INFLUENT	FLUSH MOUNT CONCRETE WALL	ОНС	24	30	24	4	4	480	SEE NOTE 1
SG-308D	UPWARD OPENING SLIDE GATE	FILTER NO 8 - DRAIN	FLUSH MOUNT CONCRETE WALL	OHC	24	72	24	9	9	480	SEE NOTE 1

CONTROL VALVE SCHEDULE								
VALVE ID	TYPE	SERVICE	SIZE (INCHES)	MAX FLOW	MAX PRESS (PSI)	OPERATION	VOLTAGE	REMARKS
BFV-302AA	BFV	FILTER NO 2 - SIDE A AIR SCOUR	8	1590 SCFM	15	OC	120	SEE NOTE 1
BFV-302WA	BFV	FILTER NO 2 - SIDE A WASHWATER	18	19 MGD	70	ОС	120	SEE NOTE 1
BFV-302M	BFV	FILTER NO 2 - BACKWASH MANIFOLD	18	19 MGD	15	ОС	120	SEE NOTE 1
FCV-302E	BFV	FILTER NO 2 - EFFLUENT	14	2.3 MGD	15	MOD	120	SEE NOTE 1
BFV-302R	BFV	FILTER NO 2 - RINSE	8	2.3 MGD	5	MOD	120	SEE NOTES 1, 4
BFV-302AB	BFV	FILTER NO 2 - SIDE B AIR SCOUR	8	1590 SCFM	15	OC	120	SEE NOTE 1
BFV-302WB	BFV	FILTER NO 2 - SIDE B WASHWATER	18	19 MGD	70	OC	120	SEE NOTE 1
BFV-308AA	BFV	FILTER NO 8 - SIDE A AIR SCOUR	8	1590 SCFM	15	ОС	120	SEE NOTE 1
BFV-308WA	BFV	FILTER NO 8 - SIDE A WASHWATER	18	19 MGD	70	OC	120	SEE NOTE 1
BFV-308M	BFV	FILTER NO 8 - BACKWASH MANIFOLD	18	19 MGD	15	OC	120	SEE NOTE 1
FCV-308E	BFV	FILTER NO 8 - EFFLUENT	12	2.3 MGD	15	MOD	120	SEE NOTE 1
BFV-308R	BFV	FILTER NO 8 - RINSE	8	2.3 MGD	5	MOD	120	SEE NOTE 1, 4
BFV-308AB	BFV	FILTER NO 8 - SIDE B AIR SCOUR	8	1590 SCFM	15	ОС	120	SEE NOTE 1
BFV-308WB	BFV	FILTER NO 8 - SIDE B WASHWATER	18	1590 SCFM	70	ОС	120	SEE NOTE 1
FCV-310E	BFV	FILTER NO 10 - EFFLUENT	12	2.3 MGD	15	MOD	120	SEE NOTE 1, 2

OPERATION LEGEND

O = OPEN C = CLOSED

H = HOLD MOD = MODULATING


	PIPELINE SCHEDULE								
MEDIA	DESCRIPTION	MATERIAL	SPEC SECTION	INSTALLATION	TEMP DEG F	TEST PRESSURE psig	TEST TYPE (H OR P)	REMARKS	
А	AIR SCOUR	SCH 10S, 304L STAINLESS STEEL	40 05 23	EXPOSED	40 - 250	25	Р		
IT	INSTRUMENTATION TURING	COPPER	40 05 00	EXPOSED	40 - 160	125	Н		

ABBREVIATION LEGEND

- H = HYDRAULIC (WATER) PRESSURE TESTING PROCEDURES P = PNEUMATIC (AIR) PRESSURE TESTING PROCEDURES

NOTES:

- 1. ALL CONTROL VALVES, GATES, AND ACTUATORS ARE TO BE OWNER PROVIDED EQUIPMENT.
- 2. CONTRACTOR TO REPLACE FILTER 10 EFFLUENT VALVE UNDER THIS CONTRACT. COORDINATE ISOLATION AND REPLACEMENT WITH THE OWNER.
- 3. TAPS TO BE USED FOR TURBIDITY ARE LOCATED BETWEEN THE FILTER WALL AND THE WASHWATER BFV. PARTICLE COUNTER AND PRESSURE AND FLOW TRANSMITTER TAPS TO BE USED ARE LOCATED ON THE FINISHED WATER PIPE. AT EACH EXISTING TAP TO BE REUSED, INSTALL A STAINLESS STEEL THREADED NIPPLE FOLLOWED BY A BALL VALVE AND COPPER TUBING TO THE NEW INSTRUMENTS AND/OR GAUGES.
- 4. CONTRACTOR TO PURCHASE AND INSTALL APT CARDS FOR FILTER RINSE VALVES TO CONVERT FROM O/C OPERATION TO MODULATING. IF APT CARD REPLACEMENT CANNOT BE ACCOMMODATED, CONTRACTOR TO PURCHASE AND INSTALL NEW MODULATING ACTUATORS. CONTACT LEE JONES WITH CHARLES-FINCH (SOUTHERN VALVE & METALS).




TNV						
	NO.	NO. DATE	REVISION		ВҮ	APVD
	DESIGN	IED BY:	DESIGNED BY: DRAWN BY:	CHECKED BY:	APPROVED BY:	BY:

DETAILS


SCELLANEOUS






FILE SEE LEFT VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING DATE MARCH 2025 PROJ. **100339.11**

M09



INSTRUMENT SYMBOLS AND LEGEND




wzzo/

SOFTWARE DEVICE NOT DISPLAYED

	FIRST LETTER		SUCCEEDIN	G LETTERS	
	MEASURED OR INITIATING VARIABLE	MODIFIER	READOUT OR PASSIVE FUNCTION	OUTPUT FUNCTION	MODIFIER
Α	ANALYSIS		ALARM		
В	BURNER FLAME				
С	CONDUCTIVITY (ELECTRICAL)			CONTROL	CLOSE
D	DENSITY (MASS) OR SPECIFIC GRAVITY	DIFFERENTIAL	DELAY		
Е	VOLTAGE (EMF)		PRIMARY ELEMENT		
F	FLOW RATE	RATIO (FRACTION)			
G	GAUGING		GLASS		
Н	HAND (MANUALLY INITIATED)				HIGH
	CURRENT (ELECTRICAL)		INDICATE		
J	POWER	SCAN			
К	TIME OR SCHEDULE			CONTROL STATION	
L	LEVEL		LIGHT (PILOT)		LOW
М	MOISTURE OR HUMIDITY	MOMENTARY			MIDDLE OR INTERMEDIATE
N	UNCLASSIFIED				
0	UNCLASSIFIED		ORIFICE (RESTRICTION)		OPEN
Р	PRESSURE OR VACUUM		POINT (TEST CONNECTION)		
Q	QUANTITY OR EVENT	INTEGRATE OR TOTALIZE			
R	RADIOACTIVITY		RECORD OR PRINT		
S	SPEED OR FREQUENCY	SAFETY		SWITCH	
Т	TEMPERATURE			TRANSMIT OR TRANSMITTER	
U	MULTIVARIABLE		MULTIFUNCTION	MULTIFUNCTION	MULTIFUNCTION
V	VIBRATION, MECHANICAL ANALYSIS			VALVE, DAMPER OR LOUVER	
W	WEIGHT OR FORCE		WELL		
Х	UNCLASSIFIED			UNCLASSIFIED	
Υ	UNCLASSIFIED			RELAY, COMPUTE OR CONVERT	
Z	POSITION			DRIVE, ACTUATE OR UNCLASSIFIED FINAL CONTROL	

INSTRUMENT IDENTIFICATION



FLOW, PIPING AND VALVE SYMBOLS

\bowtie	GATE VALVE	\overline{M}	ELECTRIC MOTOR
	BALL VALVE		
	SWING CHECK VALVE		CAP
→	BALL CHECK VALVE		FLANGES
	BUTTERFLY VALVE		CALIBRATION COLUMN
	PLUG VALVE		
	SLUICE, SLIDE OR SHEAR GATE		DIAPHRAGM PUMP
*	AIR RELEASE VALVE	AF	AIR FILTER
	PRESSURE REDUCING VALVE		ISOLATION VALVE
	ELECTRIC CHECK VALVE		THREE-WAY VALVE
M	ELECTRIC ACTUATED VALVE		PRESSURE CONTROL VALVE
	MUD OR FOOT VALVE		BACK PRESSURE VALVE
	FLOW TUBE (VENTURI)		PULSATION DAMPENER
	PARSHAL FLUME		PUMP
-M	MAGNETIC FLOW METER		PERISTALTIC PUMP
\bigcirc	ROTAMETER		DIAPHRAGM PUMP
S	SOLENOID ACTUATED VALVE		GEAR PUMP OR BLOWER (POSITIVE DISPLACEMENT)
S	SOLENOID ACTUATED DIAPHRAGM VALVE		REDUCER
\Box	PNEUMATIC ACTUATED		UNION
	DIAPHRAGM VALVE	8	MIXER
	PRESSURE RELIEF VALVE (SAFETY)		STATIC MIXER
	EDUCTOR	Y	DRAIN
- 	SILENCER		DIAPHRAGM OR LOAD CELL
	OILLIIOLI (SPACE HEATER /

PROCESS PIPING ABBREVIATIONS

_		
_		
	Α	AIR
	BW	BACKWASH
	CA	COMPRESSED AIR
	D	DRAIN
	FE	FILTER EFFLUENT
	FR	FILTER RINSE
	FW	FINISHED WATER
	PAC	POWDERED ACTIVATED CARBON
	PACS	POWDERED ACTIVATED CARBON-SLURRY

PSW PLANT SERVICE WATER

1. ALL DETAIL WIRING AND ELECTRICAL COMPONENTS ARE NOT SHOWN ON THE PROCESS AND INSTRUMENTATION DIAGRAM DRAWINGS. THE ELECTRICAL DRAWINGS ARE TO BE USED IN CONJUNCTION WITH THE PROCESS AND INSTRUMENTATION DIAGRAMS. THE PROCESS AND INSTRUMENTATION DIAGRAMS ARE PRESENTED AS A COORDINATING TOOL THAT INDICATES THE MAIN CONTROL LOGIC FOR THE PROJECT PROCESS SYSTEMS AND COMPONENTS. ACTUAL DETAIL LOGIC AND CONTROL COMPONENTS MAY DIFFER DEPENDING ON THE MANUFACTURER THAT IS AWARDED THE CONTRACT.

HEAT TRACING

- 2. SEE CIVIL AND PROCESS DRAWINGS FOR PIPING DETAILS.
- 3. SOME SYMBOLS AND INFORMATION ON THIS LEGEND MAY NOT BE USED ON THIS PROJECT.


2025.03.20 22:30:07-05'00'


Ð

RDUR FILE SEE LEFT VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING

ISSUED FOR BID

DATE MARCH 2025 PROJ. **100339.11**





ABBREVIATIONS

A OR AMP **AMPERES** UG ABOVE FINISH FLOOR AIR HANDLING UNIT UNO AIC AMPERE INTERRUPTING CAPACITY AM AMMETER **VFD** AS AMMETER SELECTION SWITCH VM **ASYM ASYMMETRICAL VMS** ATS AUTOMATIC TRANSFER SWITCH AUTOMATIC TRANSFORMER BACKUP CONTROL PANEL **BCP** WHDM CONDUIT WM CB CIRCUIT BREAKER WP CKT **CIRCUIT** XFMR CLF CURRENT LIMITING FUSE CNTL CONTROL **CURRENT TRANSFORMER DELTA CONNECTION** DISTRIBUTION PANELBOARD DS OR DISC DISCONNECT SWITCH DATA TERMINAL CABINET EXHAUST FAN EF **EQUIPMENT GROUND EMCP** ENERGY MANAGEMENT CONTROL PANEL **EGC** EQUIPMENT GROUNDING CONDUCTOR ELECTRICAL METALLIC TUBING **EMT ESTOP** EMERGENCY STOP EXISTING TO REMAIN ETR EXISTING EX OR EXIST. **EXPLOSION PROOF** EXP **FUSE** FIRE ALARM FLOAT CONTROL RELAY **FACP** FIRE ALARM CONTROL PANEL **FMPX** FIRE ALARM MULTIPLEX PANEL G OR GND GROUND GROUNDING ELECTRODE CONDUCTOR GF **GROUND FAULT** GROUND FAULT INTERRUPTING GFI HEIGHT HORSEPOWER HIGH VOLTAGE. 600VAC **HVAC** HEATING, VENTILATION AND AIR INTERMEDIATE METAL CONDUIT JB OR J JUNCTION BOX KVA KILOVOLT - AMPS KW KILOWATTS KILOWATT-HOUR LENGTH LIGHTING ARRESTOR LCP LIGHTING CONTROL PANEL **LFMC** LIQUIDTIGHT FLEXIBLE METAL CONDUIT LIGHTING PANELBOARD LOW VOLTAGE, 240VAC MCB OR MB MAIN CIRCUIT BREAKER MOTOR CONTROL CENTER MFR MANUFACTURER MH OR MTG MOUNTING HEIGHT MAIN LUG ONLY MMS MICROPROCESSOR-BASED METERING SYSTEM MT OR MTD MOUNT OR MOUNTED NEUTRAL NORMALLY CLOSED **NEC** NATIONAL ELECTRICAL CODE **NEMA** NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION NON-FUSIBLE **NFPA** NATIONAL FIRE PROTECTION ASSOCIATES NO NORMALLY OPEN NOT TO SCALE NTS POLE POWER FACTOR CAPACITOR PROGRAMMABLE LOGIC CONTROLLER **PMT** PAD MOUNT TRANSFORMER **PNL** PANEL POLYVINYLCHLORIDE CONDUIT **PVC**

REMOTE CONTROL SWITCH

RIGID GALVANIZED COUDUIT

STAINLESS STEEL, SOFT START

TEMPERATURE CONTROL PANEL

TELEPHONE TERMINAL CABINET

TRANSIENT VOLTAGE SURGE SUPPRESSOR

ROOT MEAN SQUARE

REMOTE TERMINAL UNIT

TELEPHONE BACKBOARD

REC OR RECPT RECEPTACLE

SWITCH

TYPICAL

SWITCHBOARD

SYMMETRICAL

RMS

RTU

SS

SW

SYM

TBB

TCP

TTC

TVSS

TYP

GENERAL NOTES

UNDERGROUND

VOLTS

WIDTH

VOLTMETER

WATTMETER

WEATHER PROOF

WYE CONNECTION

TRANSFORMER

UNDERWRITER'S LABORATORIES


UNLESS NOTED OTHERWISE


VARIABLE FREQUENCY DRIVE

VOLTMETER SELECTOR SWITCH

WATT HOUR DEMAND METER

- 1. ENTIRE INSTALLATION SHALL BE IN ACCORDANCE WITH THE FOLLOWING **CODES AND STANDARDS:**
- 1.1. NFPA 70, NATIONAL ELECTRICAL CODE.
- NFPA 101 LIFE SAFETY CODE.
- NFPA 820 STANDARD FOR FIRE PROTECTION IN WASTEWATER TREATMENT AND COLLECTION FACILITIES.
- 2. ALL ELECTRICAL CIRCUITS SHALL INCLUDE A GREEN GROUNDING CONDUCTOR SIZED PER NEC.
- 3. CONDUIT AND DEVICE LOCATIONS ARE SHOWN DIAGRAMMATICALLY ONLY, CONTRACTOR SHALL FIELD LOCATE OR ROUTE AS REQUIRED.
- 4. ALL CONDUIT SHALL BE INSTALLED PARALLEL AND PERPENDICULAR TO BUILDING STRUCTURE.
- 5. ALL PANEL LEGENDS SHALL BE RETYPED TO REFLECT UP TO DATE CONDITIONS. ALL PANEL LEGENDS SHALL INDICATE THE PANEL'S FEEDER CKT. SOURCE PANEL (OR SUBSTATION) AND ITS LOCATION.
- ELECTRICAL EQUIPMENT AND DEVICES SHALL BE PROVIDED WITH PHENOLIC NAMEPLATES. ALL NAMEPLATES SHALL BE MECHANICALLY FASTENED WITH S.S. SCREWS OR RIVETS. THE USE OF ADHESIVE NAMEPLATES SHALL NOT BE ALLOWED.
- 7. CONTRACTOR SHALL MAINTAIN A SET OF PRINTS AND MARK-UP DURING CONSTRUCTION TO REFLECT "AS-BUILT" CONDITIONS. PRINTS SHALL BE DELIVERED TO THE ENGINEER UPON COMPLETION OF THE PROJECT AS A COMPLETE SET OF RECORD DRAWINGS. IN ADDITION, THE CONTRACTOR SHALL PROVIDE ELECTRONIC COPIES OF ALL UPDATES "AS-BUILT" DRAWINGS IN AUTOCAD 2007 FORMAT.
- 8. THE CONTRACTOR SHALL PROVIDE PULL BOXES IN POWER CIRCUIT CONDUIT AS REQUIRED, SO AS TO LIMIT THE NUMBER OF BENDS TO A MAXIMUM OF 360 DEGREES OR FOUR 90 DEGREE TURNS.
- 9. PROVIDE CONDUIT EXPANSION FITTINGS AS CONDUIT CROSSES BUILDING **EXPANSION JOINTS.**
- 10. ALL EXTERIOR ELECTRICAL ENCLOSURES SHALL BE NEMA 4X STAINLESS STEEL UNLESS OTHERWISE NOTED.
- 11. ALL SUPPORTING AND FASTENING DEVICES SHALL BE STAINLESS STEEL
- 12. CONTRACTOR MAY COMBINE HOMERUNS TO ALL PANEL BOARDS PER NEC.
- 13. ALL RECEPTACLE BRANCH CIRCUITS OVER 75' IN LENGTH SHALL USE #10 AWG CONDUCTOR (FOR VOLTAGE DROP).
- 14. CONTRACTOR TO PROVIDE ALL REQUIRED POWER AND STARTERS FOR PROCESS EQUIPMENT (COORDINATE WITH PROCESS EQUIPMENT
- 15. CONTRACTOR SHALL PROVIDE 2 SPARE FUSES FOR EACH FUSE INSTALLED INCLUDING ALL EQUIPMENT AND CONTROLS.
- 16. CONTROL AND POWER CONDUITS SHALL BE SEPARATED BY 12" MIN. AND SHALL BE IN SEPARATE JUNCTION BOXES AND DUCT BANKS. MAINTAIN 12" SEPARATION BETWEEN DUCT BANKS.
- 17. CONTRACTOR SHALL MAINTAIN OPERATION OF THE ELECTRICAL SERVICE DURING THE UPGRADE.
- 18. THE CONTRACTOR SHALL BE RESPONSIBLE FOR READING ALL PROJECT SPECIFICATIONS AND WILL BE RESPONSIBLE FOR MEETING ALL REQUIREMENTS OUTLINED IN THE SPECIFICATIONS.
- 19. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING DETAILED ELECTRICAL EQUIPMENT LAYOUT DRAWINGS TO THE ENGINEER FOR APPROVAL PRIOR TO INSTALLATION.






CVMDIII	DESCRIPTION
SYMBOL HH	DESCRIPTION CONTACT, NORMALLY OPEN
	CONTACT, NORMALLY CLOSED
	□PERATING C□IL * DESIGNATION: C - C□NTACT□R R - C□NTR□L RELAY M - MAGNETIC M□T□R STARTER - N□N REVERSING
*	MF - MAGNETIC MUTUR STARTER - FURWARD MR - MAGNETIC MUTUR STARTER - REVERSE MU - MAGNETIC MUTUR STARTER - UPEN MC - MAGNETIC MUTUR STARTER - CLUSE MH - MAGNETIC MUTUR STARTER - HIGH SPEED ML - MAGNETIC MUTUR STARTER - LOW SPEED SUV - SULENDID UPERATED VALVE TD - TIME DELAY RELAY T - PROGRAMMABLE TIMER
ETM	METER, ELAPSED TIME
**	INDICATING LIGHT - FULL VOLTAGE TRANSFORMER OR LED * DESIGNATION: A - AMBER R - RED B - BLUE W - WHITE G - GREEN Y - YELLOW
	INDICATING LIGHT, PUSH -TO-TEST * DESIGNATION: A - AMBER R - RED B - BLUE W - WHITE G - GREEN Y - YELLOW
0 0	SWITCH, PUSHBUTTON, NORMALLY OPEN CIRCUIT
OLO TI	SWITCH, PUSHBUTTON, NORMALLY CLOSED SWITCH, PUSHBUTTON, TAG LINE,
TL olo	NORMALLY CLOSED CIRCUIT WITH MAINTAINED CONTACT
0 0	SWITCH, PUSHBUTTON, TWO CIRCUIT, NORMALLY OPEN AND NORMALLY CLOSED
ഹ്	SWITCH, EMERGENCY SHUTDOWN, MUSHROOM-HEAD PUSHBUTTON, NORMALLY CLOSED CIRCUIT WITH MAINTAINED CONTACT
H	SWITCH, MASTER OR CONTROL X - INDICATES CONTACT CLOSED
00	MDMENTARY-CONTACT SWITCH
~	SWITCH PRESSURE/VACUUM OPERATED. NORMALLY OPEN. CLOSING ON RISING PRESSURE
T	SWITCH PRESSURE/VACUUM OPERATED. NORMALLY CLOSED
~~	DPENING ON RISING PRESSURE SWITCH, FLOW ACTUATED, NORMALLY OPEN, CLOSING ON INCREASE IN FLOW
To	SWITCH, FLOW ACTUATED, NORMALLY CLOSED OPENING ON INCREASE IN FLOW
~T°	SWITCH, TEMPERATURE ACTUATED, NORMALLY CLOSED OPENING ON RISING TEMPERATURE
2	SWITCH, TEMPERATURE ACTUATED, NORMALLY OPEN CLOSING ON RISING TEMPERATURE
7°	CONTACT, TIME DELAY, NORMALLY OPEN WITH TIME DELAY CLOSING
~°	CONTACT, TIME DELAY, NORMALLY OPEN WITH TIME DELAY OPENING
T	CONTACT, TIME DELAY, NORMALLY CLOSED WITH TIME DELAY OPENING
T°	CONTACT, TIME DELAY, NORMALLY CLOSED WITH TIME DELAY CLOSING
LS	SWITCH, LIMIT
2T ₀	SWITCH, TORQUE
9	SWITCH, LIQUID LEVEL ACTUATED, CLOSING ON RISING LEVEL
To	SWITCH, LIQUID LEVEL ACTUATED, OPENING ON RISING LEVEL

SYMBOL	DESCRIPTION
25A	FUSE (AMPERE RATING SHOWN)
I/**2KV	FUSED DISCONNECT SWITCH, 3 POLE
1200A 150A	* DESIGNATION: LS - LOAD BREAK SWITCH
부	DS - DISCONNECT SWITCH
<u> </u>	POWER CIRCUIT BREAKER,
☐1200A ※	MEDIUM-VOLTAGE, DRAWOUT TYPE (AMPERE RATING SHOWN)
500AT	CIRCUIT BREAKER, DRAWOUT TYPE, 600VAC OR LESS, 3P (TRIP AND FRAME AMPERE
YOUA	RATING SHOWN)
)60AT	CIRCUIT BREAKER, THERMOMAGNETIC, 600 VAC OR LESS, 3P (AMPERE RATING
1) 600AT	SHOWN) CIRCUIT BREAKER, THERMOMAGNETIC, 600
1000AF	VAC OR LESS, 3P ADJUSTIBLE TRIP (TRIP & FRAME AMPERE RATING SHOWN)
)7A	M□T□R CIRCUIT PR□TECT□R, 600∨ AC □R LESS, 3P U□N (C□NTINU□US AMPERE RATING SH□WN)
3P 20A	CONTACTOR (NUMBER OF POLES AND AMPERE RATING SHOWN)
	MAGNETIC MOTOR STARTER
*	* NEMA SIZE ** DESIGNATION:
**	NONE - FULL VOLTAGE, NON-REVERSING FVR - FULL VOLTAGE, REVERSING
	RVNR - REDUCED VOLTAGE, NON-REVERSING
M	RVR - REDUCED VOLTAGE, REVERSING MANUAL MOTOR STARTER
	VARIABLE FREQUENCY DRIVE / INVERTER
△ ↓ 750KVA 4.16/ 0.48KV	POWER TRANSFORMER (KVA RATING, VOLTAGES AND WINDINGS CONNECTIONS SHOWN)
Z=X% υ &	SERIES REACTOR (LINE OR LOAD RATING SHOWN)
(2) \$\frac{\pm4200}{\pm120\cdot}\$	VOLTAGE TRANSFORMER (QUANTITY AND VOLTAGE RATIO SHOWN)
(3) E800/5A	CURRENT TRANSFORMER (QUANTITY AND CURRENT RATIO SHOWN)
(3) = 2200/5A SET AT	MULTI-RATIO CURRENT TRANSFORMER (QUANTITY, MAXIMUM CURRENT RATIO AND SETTING SHOWN)
1200/5A #800/5A	ZERO SEQUENCE CURRENT TRANSFORMER (CURRENT RATIO SHOWN)
	CAPACITOR
=	GROUND CONNECTION
— (3)	SURGE ARRESTER (QUANTITY SHOWN)
0 3P 400A	TRANSFER SWITCH (NUMBER OF POLES AND AMPERE RATING SHOWN)
± 125VDC	BATTERY (RATING SHOWN)
10	MOTOR, INDUCTION (HORSEPOWER SHOWN)

SYMBOL	DESCRIPTION
750KW 480V 3-PHASE	GENERATOR (KW RATINGS, VOLTAGE AND PHASE SHOWN)
\$	THERMISTOR
-	DIODE, SEMICONDUCTOR
RTD	RESISTANCE TEMPERATURE DETECTOR
ф	RESISTOR
~~~	SPACE HEATER
500VA 480/120V	CONTROL POWER TRANSFORMER, (VA RATING VOLTAGES)
AS	AMMETER SWITCH
VS VS	VOLTMETER SWITCH
[CS]	CONTROL SWITCH
*	METER  * DESIGNATION:  AM - AMMETER
*	PROTECTIVE RELAY OR DEVICE  * DESIGNATION:  11 - MULTIFUNCTION PROTECTIVE RELAY  25 - SYNCHRONIZING OR SYNCHRONISM-CHECK RELAY  26 - APPARATUS THERMAL DEVICE  27 - UNDERVOLTAGE RELAY  32 - DIRECTIONAL POWER RELAY  37 - UNDERCURRENT OR UNDERPOWER RELAY  40 - FIELD RELAY  46 - REVERSE-PHASE OR PHASE-BALANCE  CURRENT RELAY  49 - MACHINE OR TRANSFORMER THERMAL RELAY  50 - INSTANTANEOUS OVERCURRENT RELAY  50GS- INSTANTANEOUS GROUND FAULT RELAY  51 - AC TIME OVERCURRENT RELAY  510S- AC TIME GROUND FAULT RELAY  51V - AC TIME DERCURRENT RELAY  51V - AC TIME DERCURRENT RELAY  60 - VOLTAGE RESTRAINT)  55 - POWER FACTOR RELAY  60 - VOLTAGE OR CURRENT BALANCE RELAY  61 - GROUND DETECTOR RELAY  62 - PRESSURE SWITCH  63 - PRESSURE SWITCH  64 - GROUND DETECTOR RELAY  65 - AC DIRECTIONAL OVERCURRENT RELAY  86 - LOCKOUT RELAY  87 - DIFFERENTIAL PROTECTIVE RELAY  88 - DIFFERENTIAL GROUND FAULT  RELAY





	WIRING
J	JUNCTION BOX
РВ	PULL BOX
Н	HANDHOLE
PX) (CX)	CONDUIT CONDUCTOR WIRE TAG. P-DENOTES POWER C-DENOTES CONTROL CIRCUIT
	COMMUNICATION
— <u>D</u>	DATA COMMUNICATION OUTLET
<u> </u>	CABLE TELEVISION OUTLET
	DATA COMMUNICATION FLOOR OUTLET
	TELEPHONE FLOOR RECEPTACLE
M	WALL MOUNTED TELEPHONE
$\bowtie$	WALL MOUNTED DATA
S	CEILING MOUNTED SPEAKER
	<u>LIGHTING</u>
€	EXIT SIGN WALL MOUNTED LIGHT
	ELECTRIC RESISTANCE HEATER
	FLUORESCENT EMERGENCY LIGHT FIXTURE
\$	SINGLE POLE SWITCH
\$3	THREE-WAY SWITCH
\$т	TIMER OPERATED SWITCH
\$ _F	FUSED SWITCH
\$ _P	SWITCH WITH PILOT LIGHT
	CEILING MOUNTED PULL SWITCH
\$2	DOUBLE POLE SWITCH
\$4	FOUR-WAY SWITCH
\$ĸ	KEY OPERATED SWITCH
L) PS	LAMP HOLDER POLE SWITCH

	LICHTING (CONT)					
	<u>LIGHTING (CONT)</u>					
\$LM	LOW VOLTAGE MASTER SWITCH					
\$wp	WEATHER PROOF SWITCH					
<del>-</del>	INCANDESCENT CEILING MOUNTED LIGHT					
Ø	RECESSED FLUORESCENT 2X4 LIGHT FIXTURE					
	RECESSED FLUORESCENT 1X4 LIGHT FIXTURE					
	RECESSED FLUORESCENT 1X8 LIGHT FIXTURE					
0	SURFACE MOUNTED FLUORESCENT 2X4 LIGHT FIXTURE					
	SURFACE MOUNTED FLUORESCENT 1X4 LIGHT FIXTURE					
0	SURFACE MOUNTED FLUORESCENT 1X8 LIGHT FIXTURE					
X-	STREET LIGHT WITH BRACKET					
$\simeq$	EXTERIOR BUILDING LIGHT					
$\rightarrow$	EMERGENCY BATTERY POWERED LIGHTS					
0	2' X 2' LIGHT FIXTURE					
<b>├</b>	INDUSTRIAL OR STRIP FIXTURE					
*	HIGHMAST LIGHTING ASSEMBLY					
<b>\$</b>	AREA LIGHTING ASSEMBLY					

	POWER
-©	CLOCK HANGER RECEPTACLE
<b>=</b>	DUPLEX RECEPTACLE
=	DUPLEX ON EMERGENCY POWER RECEPTACLE
=⊕	DUPLEX WITH GFI RECEPTACLE
=	QUADRAPLEX RECEPTACLE
-0	SINGLE RECEPTACLE
-⊖ _S	SINGLE RECEPTACLE WITH SWITCH
	SPECIAL PURPOSE RECEPTACLE
⇒s	DUPLEX RECEPTACLE WITH SWITCH
	FLUSH MOUNTED PANELBOARD CABINET
	SURFACE MOUNTED PANELBOARD CABINET
T	TRANSFORMER


	SINGLE LINE (CONT)
Ī	EARTH GROUND
	FUSED DISCONNECT SWITCH
ㅁ	UNFUSED DISCONNECT SWITCH
( <u>M</u>	METER
DP#_	DISTRIBUTION PANEL
LP#_	LIGHTING PANEL
PP#_	POWER PANEL





DATE MARCH 2025
PROJ. 100339.11

E03



1. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR REQUIRED FOR THE INSTALLATION OF FILTERS 2 & 8 AS DETAILED ON THE PROJECT PLANS. FILTERS 1 & 7 WERE COMPLETED ON A PREVIOUS PROJECT. FILTERS 3, 4, 5, 6, 9, & 10 ARE NOT INCLUDED IN THIS PROJECT AND HAVE BEEN SHOWN FOR CLARITY. THE MATERIAL TYPES, INSTALLATION METHODS, AND QUALITY OF WORK PERFORMED FOR FILTERS 1 & 7 SHALL BE IMPLEMENTED FOR FILTERS 2 & 8.

# No. 39545 PROFESSIONA 2025.03.20 22:31:38-05'00'

# **KEY NOTES:**

- $\langle A \rangle$  PANEL HF1 (EXISTING). 125A, 480/277V, 3ø, 4W, 42 CIRCUIT DISTRIBUTION PANELBOARD. SEE HF PANEL SCHEDULE DRAWING FOR CIRCUIT DETAILS. THE CONTRACTOR SHALL UTILIZE SPARE BREAKERS TO SUPPLY ALL NEW LOADS ASSOCIATED WITH THIS PHASE (FILTERS 2 & 8 ADDITIONS).
- $\langle B \rangle$  TRANSFORMER TF1 (EXISTING). 45KVA, 480-208/120V TRANSFORMER.
- $\langle C \rangle$  PANEL LF1 (EXISTING). 125A, 208/120V, 3ø, 4W, 125A MAIN CIRCUIT BREAKER, 30 CIRCUIT DISTRIBUTION PANELBOARD. SEE LF1 PANEL SCHEDULE FOR CIRCUIT DETAILS. THE CONTRACTOR SHALL UTILIZE SPARE BREAKERS TO SUPPLY ALL NEW LOADS ASSOCIATED WITH THIS PHASE (FILTERS 2 & 8 ADDITIONS).
- $\langle D \rangle$  PANEL HF2 (EXISTING). 125A, 480/277V, 3ø, 4W, 42 CIRCUIT DISTRIBUTION PANELBOARD. SEE HF PANEL SCHEDULE DRAWING FOR CIRCUIT DETAILS. THE CONTRACTOR SHALL UTILIZE SPARE BREAKERS TO SUPPLY ALL NEW LOADS ASSOCIATED WITH THIS PHASE (FILTERS 2 & 8 ADDITIONS).
- $\langle E \rangle$  TRANSFORMER TF2 (EXISTING). 45KVA, 480-208/120V TRANSFORMER.
- (F) PANEL LF4 (EXISTING). 125A, 208/120V, 3ø, 4W, 125A MAIN CIRCUIT BREAKER, 30 CIRCUIT DISTRIBUTION PANELBOARD. SEE LF4 PANEL SCHEDULE FOR CIRCUIT DETAILS. THE CONTRACTOR SHALL UTILIZE SPARE BREAKERS TO SUPPLY ALL NEW LOADS ASSOCIATED WITH THIS PHASE (FILTERS 2 & 8 ADDITIONS).
- $\langle G \rangle$  PANEL LF5 (EXISTING). 125A, 208/120V, 3ø, 4W, 125A MAIN CIRCUIT BREAKER, 30 CIRCUIT DISTRIBUTION PANELBOARD. WORK ASSOCIATED WITH PANEL LF5 IS NOT INCLUDED IN THE SCOPE OF THIS PHASE. PANEL LF5 SHALL FEED FUTURE REHABILITATED FILTERS 9 & 10.
- (H) PANEL LF2 (FUTURE). 125A, 208/120V, 3ø, 4W, 125A MAIN CIRCUIT BREAKER, 30 CIRCUIT DISTRIBUTION PANELBOARD. WORK ASSOCIATED WITH PANEL LF2 IS NOT INCLUDED IN THE SCOPE OF THIS PHASE. PANEL LF2 SHALL FEED FUTURE REHABILITATED FILTERS 3 & 4.
- (I)PANEL LF3 (FUTURE). 125A, 208/120V, 3ø, 4W, 125A MAIN CIRCUIT BREAKER, 30 CIRCUIT DISTRIBUTION PANELBOARD. WORK ASSOCIATED WITH PANEL LF2 IS NOT INCLUDED IN THE SCOPE OF THIS PHASE. PANEL LF2 SHALL FEED FUTURE REHABILITATED FILTERS 5 & 6.


3#8, 1#8 N, 1#10G IN A 1" C

3#12, 1#12G IN A 3/4" C

1#12, 1#12 N, 1#12G IN A 3/4" C

SCALE: NONE

AND CONDUCTOR



A UTILITIES DEPARTMENT /E WATER TREATMENT PLA IODIFICATIONS - PHASE 2 ISTA L AVE R MOI IUS ID, ER HIG

LELINE


9

SIN

M

Δ






FILE SEE LEFT


**VERIFY SCALE** BAR IS ONE INCH ON ORIGINAL DRAWING

DATE MARCH 2025 PROJ. 100339.11



### **KEY NOTES:**

(A) PLANT SCADA SYSTEM HMI (EXISTING). THE CONTRACTOR SHALL PROVIDE ALL HMI PROGRAMMING AND CONFIGURATION NECESSARY TO INCORPORATE THE NEW FILTERS INTO THE EXISTING PLANT SCADA SYSTEM HMI. INTEGRATION AND REPRESENTATION OF THE NEW FILTERS INTO THE PLANT HMI SHALL MATCH FILTERS 1 & 7 WHICH WERE RECENTLY REHABILITATED. ANY LICENSE OR TAG COUNT UPGRADES NECESSARY TO HANDLE THE INTEGRATION OF THE NEW FILTERS SHALL BE PROVIDED BY THE CONTRACTOR.



 $\langle$  C angle filter control console 1/2 (existing). THE EXISTING FILTER CONTROL CONSOLE SHALL BE MODIFIED BY THE CONTRACTOR TO INCORPORATE ALL OF THE VALVES, INSTRUMENTS, AND DEVICES AS SHOWN TO MONITOR AND CONTROL THE ADDITIONAL THE CONTRACTOR SHALL PROVIDE ALL NECESSARY MODIFICATIONS, PLC PROGRAMMING, AND LOCAL HMI PROGRAMMING TO FULLY INCORPORATE ADDITIONAL FILTER COMPONENTS INTO THE CONTROL CONSOLE. WITHIN THE CONSOLE, AT A MINIMUM, THE CONTRACTOR SHALL ADD A NETWORK SWITCH TO FACILITATE INTERCONNECTION OF THE ADDITIONAL VALVES, PROVIDE POWER FOR THE LEVEL CONTROLLERS, AND PHYSICAL INSTALLATION OF THE LEVEL CONTROLLERS IN THE CONSOLE. ALL CONFIGURATION AND PROGRAMMING SHALL MATCH WHAT WAS USED IN THE PREVIOUS PROJECT FOR EXISTING FILTERS 1 & 7.

CAT6E CABLE, 3/4" C

2#16 TSP CABLE IN A 3/4" C

FIBER OPTIC CABLE, MATCH EXISTING

MANUFACTURER CABLE, CONDUIT AS REQ.

SCALE: NONE


CONDUIT AND CONDUCTOR SCHEDULE


2025.03.20 22:32:51-05'00'

A UTILITIES DEPARTMENT
VE WATER TREATMENT PLA
IODIFICATIONS - PHASE 2 SINGLELINE ONTROL 


FILE SEE LEFT VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING

DATE MARCH 2025 PROJ. 100339.11 E05





 $\langle A \rangle$  PLC-5 CONTROL PANEL (EXISTING). THE CONTRACTOR SHALL PROVIDE ALL PLC PROGRAMMING NECESSARY TO INCORPORATE THE NEW FILTERS INTO THE OVERALL PLANT OPERATIONAL LOGIC. PROGRAMMING FOR THE NEW FILTERS SHALL MATCH WHAT WAS



(C) FILTER CONTROL CONSOLE 9/10 (FUTURE). WORK ASSOCIATED WITH THIS FILTER CONSOLE IS NOT INCLUDED IN THE SCOPE OF THIS PROJECT. IT HAS BEEN SHOWN TO DETAIL THE COMPLETE BUILD OUT FOR FILTER



ONTROL EPARTMENT EATMENT PL JS - PHASE 2 SINGLELIN ISTA L AVE R MOI GUS ND / TER AUG HIGHLAI FIL FCC



FILE SEE LEFT **VERIFY SCALE** BAR IS ONE INCH ON ORIGINAL DRAWING


DATE MARCH 2025 PROJ. **100339.11** 

E07


3	PH		WIRE VOLTAGE	L-L:	480	L-N:	277	MAIN:	125A MLO			
OCATION:	FILTER GAL	LERY			PHASE	PHASE	PHASE		MOUNTING: SURFACE			
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#
1	20	3	FILTER 1 SLUICE GATE SG-301I	305	610			305	FILTER 4 SLUICE GATE SG-304I (FUTURE)	3	20	2
3	-	-		305		610		305		-	-	4
5	-	-		305			610	305		-	-	6
7	20	3	FILTER 1 SLUICE GATE SG-301D	305	610			305	FILTER 4 SLUICE GATE SG-304D (FUTURE)	3	20	8
9	-	-		305		610		305		-	-	10
11	-	-		305			610	305		-	-	12
13	20	3	FILTER 2 SLUICE GATE SG-302I	305	305			0	SPARE	3	50	14
15	-	-		305		305		0		-	-	16
17	-	-		305			305	0		-	-	18
19	20	3	FILTER 2 SLUICE GATE SG-302D	305	305			0	SPARE	3	20	20
21	-	-		305		305		0		-	-	22
23	-	-		305			305	0		-	-	24
25	20	3	FILTER 3 SLUICE GATE SG-303I (FUTURE)	305	8785			8480	TRANSFORMER TF1	3	50	26
27	-	-		305		5601		5296		-	-	28
29	-	-		305			5601	5296		-	-	30
31	20	3	FILTER 3 SLUICE GATE SG-303D (FUTURE)	305	305			0	SPACE	-	-	32
33	-	-		305		305		0	SPACE	-	-	34
35	-	-		305			305	0	SPACE	-	-	36
37	-	-	SPACE	0	0			0	SPACE	-	-	38
39	-	-	SPACE	0		0		0	SPACE	-	-	40
41	-	-	SPACE	0			0	0	SPACE	-	-	42
TOTAL LOAD(VA)/PHASE THIS PANEL:					10920	7736	7736					
							•	_				
TOTAL CONNECTED LOAD(VA) THIS PANEL:					26392		TOTAL CON	NECTED LOAD (AN	MPS):	32		
TOTAL DEMAND LOAD (VA) THIS PANEL:					21113.6		TOTAL DEM	AND LOADS (AMP	S):	25		
OTES:												




	PH	4	WIRE VOLTAGE	L-L:	480	L-N:	277	MAIN:	125A MLO			
OCATION: FILTER GALLERY					PHASE	PHASE	PHASE		MOUNTING: SURFACE			
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#
1	20	3	FILTER 7 SLUICE GATE SG-301I	305	610			305	FILTER 10 SLUICE GATE SG-310D (FUTURE)	3	20	2
3	-	-		305		610		305		-	-	4
5	-	-		305			610	305		-	-	6
7	20	3	FILTER 7 SLUICE GATE SG-301D	305	610			305	FILTER 5 SLUICE GATE SG-305D (FUTURE)	3	20	8
9	-	-		305		610		305		-	-	10
11	-	-		305			610	305		-	-	12
13	20	3	FILTER 8 SLUICE GATE SG-308I	305	610			305	FILTER 5 SLUICE GATE SG-305I (FUTURE)	3	50	14
15	-	-		305		610		305		-	-	16
17	-	-		305			610	305		-	-	18
19	20	3	FILTER 8 SLUICE GATE SG-308D	305	610			305	SPARE	3	20	20
21	-	-		305		610		305		-	-	22
23	-	-		305			610	305		-	-	24
25	20	3	FILTER 9 SLUICE GATE SG-309I (FUTURE)	305	8785			8480	TRANSFORMER TF2	3	40	26
27	-	-		305		5601		5296		-	-	28
29	-	-		305			5601	5296		-	-	30
31	20	3	FILTER 9 SLUICE GATE SG-309D (FUTURE)	305	610			305	FILTER 6 SLUICE GATE SG-306D (FUTURE)	3	20	32
33	-	-		305		610		305		-	-	34
35	-	-		305			610	305		-	-	36
37	20	3	FILTER 10 SLUICE GATE SG-310I (FUTURE)	305	610			305	FILTER 6 SLUICE GATE SG-306I (FUTURE)	3	50	38
39	-	-		305		610		305		-	-	40
41	-	-		305			610	305		-	-	42
OTAL LOAD(VA)/PHASE THIS PANEL:			12445	9261	9261		•	•	•	•		
								_				
OTAL CON	NECTED LO	AD(VA) THIS	PANEL:		30967		TOTAL CONI	NECTED LOAD (AM	MPS):	37		
OTAL DEM	MAND LOAD (	VA) THIS PA	NEL:		24773.6		TOTAL DEMA	AND LOADS (AMP	S):	30		



THE CONTRACTOR SHALL UTILIZE THE EXISTING SPARE BREAKERS LOCATED IN PANELS HF1 & HF2 TO PROVIDE POWER FOR THE LOADS ASSOCIATED WITH FILTERS 2 & 8. FUTURE LOADS FOR FILTERS 3, 4, 5, 6, 9 & 10 HAVE BEEN SHOWN FOR THE SUBSEQUENT PROJECT PHASES.





FILE SEE LEFT VERIFY SCALE

BAR IS ONE INCH ON ORIGINAL DRAWING

0 1" DATE MARCH 2025 PROJ. 100339.11

E08

3	PH	4	WIRE VOLTAGE	L-L:	208	L-N:	120	MAIN:	125A MCB			
LOCATION: FILTER GALLERY				PHASE	PHASE	PHASE		MOUNTING: SURFACE				
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	СКТ#
1	20	1	FILTER 2 VALVE ACTUATOR - BFV-302AA	528	1056			528	FILTER 1 VALVE ACTUATOR - BFV-301AA	1	20	2
3	20	1	FILTER 2 VALVE ACTUATOR - BFV-302WA	696		1392		696	FILTER 1 VALVE ACTUATOR - BFV-301WA	1	20	4
5	20	1	FILTER 2 VALVE ACTUATOR - BFV-302M	696			1392	696	FILTER 1 VALVE ACTUATOR - BFV-301M	1	20	6
7	20	1	FILTER 2 VALVE ACTUATOR - FCV-302E	696	1392			696	FILTER 1 VALVE ACTUATOR - FCV-301E	1	20	8
9	20	1	FILTER 2 VALVE ACTUATOR - BFV-302R	528		1056		528	FILTER 1 VALVE ACTUATOR - BFV-301R	1	20	10
11	20	1	FILTER 2 VALVE ACTUATOR - BFV-302AB	528			1056	528	FILTER 1 VALVE ACTUATOR - BFV-301AB	1	20	12
13	20	1	FILTER 2 VALVE ACTUATOR - BFV-302WB	696	1392			696	FILTER 1 VALVE ACTUATOR - BFV-301WB	1	20	14
15	20	1	FILTER 2 SIDE A TURBIDITY - AIT-302A	100		200		100	FILTER 1 SIDE A TURBIDITY - AIT-301A	1	20	16
17	20	1	FILTER 2 SIDE B TURBIDITY - AIT-302B	100			200	100	FILTER 1 SIDE B TURBIDITY - AIT-301B	1	20	18
19	20	1	FILTER 2 PARTICLE COUNTER - AIT-302C	200	400			200	FILTER 1 PARTICLE COUNTER - AIT-301C	1	20	20
21	20	1	SPARE	0		0		0	SPARE	1	20	22
23	20	1	SPARE	0			0	0	SPARE	1	20	24
25	20	1	SPARE	0	0			0	SPARE	1	20	26
27	20	1	SPARE	0		0		0	SPARE	1	20	28
29	20	1	SPARE	0			0	0	SPARE	1	20	30
OTAL LOA	D(VA)/PHASI	THIS PANE	iL:	•	4240	2648	2648					
TAL CON	NECTED LO	AD(VA) THIS	PANEL:		9536		TOTAL CON	NECTED LOAD (AN	MPS):	26		
ΓΟΤΑL CONNECTED LOAD(VA) THIS PANEL: ΓΟΤΑL DEMAND LOAD (VA) THIS PANEL:					7628.8		TOTAL DEMAND LOADS (AMPS):			21		
TES:		,			7 020.0				,			

PANEL LF1	(EXISTING)
SCALE: NONE	

					PANEL:	LF2 (F	JTURE)						
3	3 PH 4 WIRE VOLTAGE L-L				L: 208 L-N: 120			MAIN:	125A MCB				
LOCATION:	FILTER GAL	LERY			PHASE	PHASE PHASE			MOUNTING: SURFACE				
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#	
1	20	1	FILTER 4 VALVE ACTUATOR - BFV-304AA	528	1056			528	FILTER 3 VALVE ACTUATOR - BFV-303AA	1	20	2	
3	20	1	FILTER 4 VALVE ACTUATOR - BFV-304WA	696		1392		696	FILTER 3 VALVE ACTUATOR - BFV-303WA	1	20	4	
5	20	1	FILTER 4 VALVE ACTUATOR - BFV-304M	696			1392	696	FILTER 3 VALVE ACTUATOR - BFV-303M	1	20	6	
7	20	1	FILTER 4 VALVE ACTUATOR - FCV-304E	696	1392			696	FILTER 3 VALVE ACTUATOR - FCV-303E	1	20	8	
9	20	1	FILTER 4 VALVE ACTUATOR - BFV-304R	528		1056		528	FILTER 3 VALVE ACTUATOR - BFV-303R	1	20	10	
11	20	1	FILTER 4 VALVE ACTUATOR - BFV-304AB	528			1056	528	FILTER 3 VALVE ACTUATOR - BFV-303AB	1	20	12	
13	20	1	FILTER 4 VALVE ACTUATOR - BFV-304WB	696	1392			696	FILTER 3 VALVE ACTUATOR - BFV-303WB	1	20	14	
15	20	1	FILTER 4 SIDE A TURBIDITY - AIT-304A	100		200		100	FILTER 3 SIDE A TURBIDITY - AIT-303A	1	20	16	
17	20	1	FILTER 4 SIDE B TURBIDITY - AIT-304B	100			200	100	FILTER 3 SIDE B TURBIDITY - AIT-303B	1	20	18	
19	20	1	FILTER 4 PARTICLE COUNTER - AIT-304C	200	400			200	FILTER 3 PARTICLE COUNTER - AIT-303C	1	20	20	
21	20	1	SPARE	0		0		0	SPARE	1	20	22	
23	20	1	SPARE	0			0	0	SPARE	1	20	24	
25	20	1	SPARE	0	0			0	SPARE	1	20	26	
27	20	1	SPARE	0		0		0	SPARE	1	20	28	
29	20	1	SPARE	0			0	0	SPARE	1	20	30	
TOTAL LOA	D(VA)/PHASI	THIS PANE	L:		4240	2648	2648		•	•		•	
								_					
TOTAL CON	OTAL CONNECTED LOAD(VA) THIS PANEL:				9536		TOTAL CONNECTED LOAD (AMPS):			26			
<b>TOTAL DEM</b>	OTAL DEMAND LOAD (VA) THIS PANEL:				7628.8		TOTAL DEMA	AND LOADS (AMPS	5):	21			



- THE CONTRACTOR SHALL UTILIZE EXISTING SPARE BREAKERS LOCATED IN PANEL LF1 TO PROVIDE POWER FOR THE LOADS ASSOCIATED WITH FILTER 2.
- 2. PANEL LF2, WHICH WILL PROVIDE POWER FOR LOADS ASSOCIATED WITH FILTERS 3 & 4 IN A SUBSEQUENT PROJECT PHASE, WILL NOT BE PROVIDED AS PART OF THIS PROJECT.




<b>—</b>
NO. DATE DESIGNED BY:
REVISION  CHECKED BY:  RAM  RAM
BY APVD APPROVED BY:
APVD BY: JD

& LF2 PANEL SCHEDULES

UGUSTA UTILITIES DEPARTMEN

AND AVE WATER TREATMENT

Water Is Life
AUGUSTA UTILITIES



FILE SEE LEFT

VERIFY SCALE

BAR IS ONE INCH ON ORIGINAL DRAWING

0 1"

DATE MARCH 2025

DATE MARCH 2025
PROJ. 100339.11

BID DWG. E09

3	3 PH 4 WIRE VOLTAGE L					L-L: 208 L-N: 120			125A MCB			
OCATION:	FILTER GALI	LERY			PHASE	PHASE	PHASE		MOUNTING: SURFACE			
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#
1	20	1	FILTER 6 VALVE ACTUATOR - BFV-306AA	528	1056			528	FILTER 5 VALVE ACTUATOR - BFV-305AA	1	20	2
3	20	1	FILTER 6 VALVE ACTUATOR - BFV-306WA	696		1392		696	FILTER 5 VALVE ACTUATOR - BFV-305WA	1	20	4
5	20	1	FILTER 6 VALVE ACTUATOR - BFV-306M	696			1392	696	FILTER 5 VALVE ACTUATOR - BFV-305M	1	20	6
7	20	1	FILTER 6 VALVE ACTUATOR - FCV-306E	696	1392			696	FILTER 5 VALVE ACTUATOR - FCV-305E	1	20	8
9	20	1	FILTER 6 VALVE ACTUATOR - BFV-306R	528		1056		528	FILTER 5 VALVE ACTUATOR - BFV-305R	1	20	10
11	20	1	FILTER 6 VALVE ACTUATOR - BFV-306AB	528			1056	528	FILTER 5 VALVE ACTUATOR - BFV-305AB	1	20	12
13	20	1	FILTER 6 VALVE ACTUATOR - BFV-306WB	696	1392			696	FILTER 5 VALVE ACTUATOR - BFV-305WB	1	20	14
15	20	1	FILTER 6 SIDE A TURBIDITY - AIT-306A	100		200		100	FILTER 5 SIDE A TURBIDITY - AIT-305A	1	20	16
17	20	1	FILTER 6 SIDE B TURBIDITY - AIT-306B	100			200	100	FILTER 5 SIDE B TURBIDITY - AIT-305B	1	20	18
19	20	1	FILTER 6 PARTICLE COUNTER - AIT-306C	200	400			200	FILTER 5 PARTICLE COUNTER - AIT-305C	1	20	20
21	20	1	SPARE	0		0		0	SPARE	1	20	22
23	20	1	SPARE	0			0	0	SPARE	1	20	24
25	20	1	SPARE	0	0			0	SPARE	1	20	26
27	20	1	SPARE	0		0		0	SPARE	1	20	28
29	20	1	SPARE	0			0	0	SPARE	1	20	30
TAL LOA	D(VA)/PHASE	E THIS PANE	EL:	,	4240	2648	2648				•	-
							•					
TAL CON	NEOTEDIO	AD(VA) TINO	DANIEL.				TOTAL CON	NECTED LOAD (AA	4DO)-			
OTAL CONNECTED LOAD(VA) THIS PANEL: OTAL DEMAND LOAD (VA) THIS PANEL:					9536			NECTED LOAD (AMB		26		
OTAL DEM	AND LOAD (	VA) THIS PA	NEL:		7628.8		IOIAL DEM	AND LOADS (AMP	5):	21		



3 PH 4 WIRE VOLTAGE L				L-L:	L-L: 208 L-N: 120			MAIN:				
OCATION:	FILTER GAL	LERY			PHASE	PHASE PHASE			MOUNTING: SURFACE			
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#
1	40	1	PANEL LF5	0	528			528	FILTER 7 VALVE ACTUATOR - BFV-307AA	1	20	2
3	-	-		0		696		696	FILTER 7 VALVE ACTUATOR - BFV-307WA	1	20	4
5	-	-		0			696	696	FILTER 7 VALVE ACTUATOR - BFV-307M	1	20	6
7	20	1	FILTER 8 VALVE ACTUATOR - BFV-308AA	528	1224			696	FILTER 7 VALVE ACTUATOR - BFV-307E	1	20	8
9	20	1	FILTER 8 VALVE ACTUATOR - BFV-308WA	696		1224		528	FILTER 7 VALVE ACTUATOR - BFV-307R	1	20	10
11	20	1	FILTER 8 VALVE ACTUATOR - BFV-308M	696			1224	528	FILTER 7 VALVE ACTUATOR - BFV-307AB	1	20	12
13	20	1	FILTER 8 VALVE ACTUATOR - BFV-308E	696	1392			696	FILTER 7 VALVE ACTUATOR - BFV-307WB	1	20	14
15	20	1	FILTER 8 VALVE ACTUATOR - BFV-308R	528		628		100	FILTER 7 SIDE A TURBIDITY - AIT-307A	1	20	16
17	20	1	FILTER 8 VALVE ACTUATOR - BFV-308AB	528			628	100	FILTER 7 SIDE B TURBIDITY - AIT-307B	1	20	18
19	20	1	FILTER 8 VALVE ACTUATOR - BFV-308WB	696	896			200	FILTER 7 PARTICLE COUNTER - AIT-307C	1	20	20
21	20	1	FILTER 8 SIDE A TURBIDITY - AIT-308A	100		100		0	SPARE	1	20	22
23	20	1	FILTER 8 SIDE B TURBIDITY - AIT-308B	100			100	0	SPARE	1	20	24
25	20	1	FILTER 8 PARTICLE COUNTER - AIT-308C	200	200			0	SPARE	1	20	26
27	20	1	SPARE	0		0		0	SPARE	1	20	28
29	20	1	SPARE	0			0	0	SPARE	1	20	30
OTAL LOA	D(VA)/PHASI	E THIS PANE	L:		4240	2648	2648					

TOTAL CONNECTED LOAD(VA) THIS PANEL:

9536

TOTAL CONNECTED LOAD (AMPS):

26

TOTAL DEMAND LOAD (VA) THIS PANEL:

7628.8

TOTAL DEMAND LOADS (AMPS):

21

NOTES

1



# **GENERAL NOTES:**

- THE CONTRACTOR SHALL UTILIZE EXISTING SPARE BREAKERS LOCATED IN PANEL LF4 TO PROVIDE POWER FOR THE LOADS ASSOCIATED WITH FILTER 8.
- 2. PANEL LF3, WHICH WILL PROVIDE POWER FOR LOADS ASSOCIATED WITH FILTERS 5 & 6 IN A SUBSEQUENT PROJECT PHASE, WILL NOT BE PROVIDED AS PART OF THIS PROJECT.



2025.03.20 22:36:19-05'00'

NO. DATE REVISION BY:

DESIGNED BY:

DESIGNE

F4 PANEL SCHEDULES
STA UTILITIES DEPARTMENT

Water Is Life
AUGUSTA UTILITIES

ARDURRA
COLLABORATE. INNOVATE. CREATE.
973 BROAD STREET, SUITE A
AUGUSTA, GA. 30901
PH (706) 664-0664
COA: PEF004730

FILE SEE LEFT

VERIFY SCALE

BAR IS ONE INCH ON ORIGINAL DRAWING

0 1"


DATE MARCH 2025
PROJ. 100339.11

DWG. E10

3 PH 4 WIRE VOLTAGE L-I				208	8 L-N: 120		MAIN:	60A MCB				
OCATION:	FILTER GAL	LERY			PHASE	PHASE	PHASE		MOUNTING: SURFACE			
CKT#	BKR.	POLE	DESCRIPTION	VOLT-AMP	Α	В	С	VOLT-AMP	DESCRIPTION	POLE	BKR.	CKT#
1	20	1	FILTER 10 VALVE ACTUATOR - BFV-310AA	528	1056			528	FILTER 9 VALVE ACTUATOR - BFV-309AA	1	20	2
3	20	1	FILTER 10 VALVE ACTUATOR - BFV-310WA	696		1392		696	FILTER 9 VALVE ACTUATOR - BFV-309WA	1	20	4
5	20	1	FILTER 10 VALVE ACTUATOR - BFV-310M	696			1392	696	FILTER 9 VALVE ACTUATOR - BFV-309M	1	20	6
7	20	1	FILTER 10 VALVE ACTUATOR - BFV-310E	696	1392			696	FILTER 9 VALVE ACTUATOR - BFV-309E	1	20	8
9	20	1	FILTER 10 VALVE ACTUATOR - BFV-310R	528		1056		528	FILTER 9 VALVE ACTUATOR - BFV-309R	1	20	10
11	20	1	FILTER 10 VALVE ACTUATOR - BFV-310AB	528			1056	528	FILTER 9 VALVE ACTUATOR - BFV-309AB	1	20	12
13	20	1	FILTER 10 VALVE ACTUATOR - BFV-310WB	696	1392			696	FILTER 9 VALVE ACTUATOR - BFV-309WB	1	20	14
15	20	1	FILTER 10 SIDE A TURBIDITY - AIT-310A	100		200		100	FILTER 9 SIDE A TURBIDITY - AIT-309A	1	20	16
17	20	1	FILTER 10 SIDE B TURBIDITY - AIT-310B	100			200	100	FILTER 9 SIDE B TURBIDITY - AIT-309B	1	20	18
19	20	1	FILTER 10 PARTICLE COUNTER - AIT-310C	200	400			200	FILTER 9 PARTICLE COUNTER - AIT-309C	1	20	20
21	20	1	SPARE	0		0		0	SPARE	1	20	22
23	20	1	SPARE	0			0	0	SPARE	1	20	24
25	20	1	SPARE	0	0			0	SPARE	1	20	26
27	20	2	GATE MOTOR	1920		1920		0	SPARE	1	20	28
29	-	-		1920			1920	0	SPARE	1	20	30
OTAL LOA	OTAL LOAD(VA)/PHASE THIS PANEL:				4240	4568	4568					
OTAL CONNECTED LOAD(VA) THIS PANEL:				13376	3376 TOTAL CONNECTED LOAD (AMPS):					37		
OTAL DEMAND LOAD (VA) THIS PANEL:				10700.8	10700.8 TOTAL DEMAND LOADS (AMPS):					30		




 EXISTING PANEL LF5 WILL PROVIDE POWER FOR LOADS ASSOCIATED WITH FILTERS 9 & 10 IN A SUBSEQUENT PROJECT PHASE. INTERCONNECTION WITH THIS PANEL IS NOT REQUIRED FOR THIS PROJECT.



NO. DATE REVISION BY: CHECKED BY: APVD DESIGNED BY: APVD APVD BY: APPDD BY: APPDD BY: APPDD BY: APPDD BY: APPDD BY: APPDD BY: APPROVED BY: APPDD BY: APPROVED BY: APPROVED BY: APPROVED BY: APPROVED BY: APPDD BY: APPROVED BY: APPDD BY: APPD BY: APPDD BY: APPD BY

5 PANEL SCHEDULE
USTA UTILITIES DEPART

Water Is Life
AUGUSTA UTILITIES



FILE SEE LEFT


VERIFY SCALE

BAR IS ONE INCH ON ORIGINAL DRAWING

0 1"

DATE MARCH 2025
PROJ. 100339.11

BID DWG. E11




2025.03.20 22:36:46-05'00'


PLAN GUSTA UTILITIES DEPARTMENT ND AVE WATER TREATMENT PL TER MODIFICATIONS - PHASE 2 FLOOR FILTER RICAL

FILE SEE LEFT VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING

PROJ. 100339.11

E12





FILTER NO.2 UPPER LEVEL ELECTRICAL PLAN

SCALE: 1/4" = 1'-0"

# **GENERAL NOTES:**

- 1. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR REQUIRED FOR THE INSTALLATION OF FILTER 2 AS DETAILED ON THE PROJECT PLANS.
- 2. USE STAINLESS STEEL UNISTRUT MOUNTED TO HANDRAILS TO SUPPORT INSTRUMENTATION.
- 3. THE CONTRACTOR SHALL REMOVE THE EXISTING FILTER 2 CONSOLE AND OLD INSTRUMENTATION. THE CONTRACTOR SHALL COORDINATE WITH THE OWNER REGARDING DISPOSAL OF ALL MATERIALS ALL MATERIALS.
- 4. PVC COATED CONDUIT SHALL BE UTILIZED IN THE FILTER GALLERY TO MATCH EXISTING.
- 5. RIGID INTERMEDIATE METALLIC CONDUIT (IMC) SHALL BE USED IN IN THE FILTER PIPE GALLERY TO MATCH EXISTING.
- 6. SEE DRAWING MO9 FOR TURBIDITY AND PARTICLE COUNTER INSTRUMENTATION RACK DETAIL.

# **KEY NOTES:**

- A INFLUENT SLUICE GATE SG-3021
- B DRAIN SLUICE GATE SG-302D
- (C) AIR SCOUR VALVE SIDE A BFV-302AA
- $\langle D \rangle$  BACKWASH VALVE SIDE A BFV-302WA
- (E) MASTER VALVE BFV-302M
- $\langle F \rangle$  EFFLUENT VALVE FCV-302E
- $\langle G \rangle$  RINSE VALVE BFV-302R
- (H) AIR SCOUR VALVE SIDE B BFV-302AB
- (I) BACKWASH VALVE SIDE B BFV-302WB
- $\langle J \rangle$  TURBIDITY METER, SIDE A AIT-302A
- (K) TURBIDITY METER, SIDE B AIT-302B
- L PARTICLE COUNTER AIT-302C
- $\langle M \rangle$  SIDE A LEVEL TRANSDUCER LE-302A
- $\langle N \rangle$  SIDE A LEVEL CONTROLLER LIT-302A (0) SIDE B LEVEL TRANSDUCER LE-302B
- $\langle P \rangle$  SIDE B LEVEL CONTROLLER LIT-302B
- $\mathbb{Q}$  EFFLUENT FLOW FIT-302
- R DIFFERENTIAL PRESSURE (HEAD LOSS) PDIT-302
- R FILTER CONTROL CONSOLE 1/2 (FCC 1/2) (EXISTING)
- $\langle S \rangle$  PANEL LF-1 (EXISTING)
- T EXISTING FILTER CONTROL CONSOLE. TO BE REMOVED.




2025.03.20 22:37:00-05'00'

			₹	m	
			BY	APPROVED BY	
			7	HECKED BY:	AB
			REVISION	DRAWN BY	KAM
			NO. DATE	ED BY:	an Br
			NO.	DESIGN	

GUSTA UTILITIES DEPARTMENT ND AVE WATER TREATMENT PL TER MODIFICATIONS - PHASE 2 PLAN ELECTRICAL 7 **TER** 







FILE SEE LEFT **VERIFY SCALE** BAR IS ONE INCH ON ORIGINAL DRAWING

DATE MARCH 2025 PROJ. 100339.11

E13






FILTER NO.8 SECTION ELECTRICAL PLAN

FILTER NO.8 LOWER LEVEL ELECTRICAL PLAN

SCALE: 1/4" = 1'-0"

SCALE: 1/4" = 1'-0"




SCALE: 1/4" = 1'-0"

# **GENERAL NOTES:**

- 1. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR REQUIRED FOR THE INSTALLATION OF FILTER 8 AS DETAILED ON THE PROJECT PLANS.
- 2. USE STAINLESS STEEL UNISTRUT MOUNTED TO HANDRAILS TO SUPPORT INSTRUMENTATION.
- 3. THE CONTRACTOR SHALL REMOVE THE EXISTING FILTER 8 CONSOLE AND OLD INSTRUMENTATION. THE CONTRACTOR SHALL COORDINATE WITH THE OWNER REGARDING DISPOSAL OF ALL MATERIALS ALL MATERIALS.
- 4. PVC COATED CONDUIT SHALL BE UTILIZED IN THE FILTER GALLERY TO MATCH EXISTING.
- 5. RIGID INTERMEDIATE METALLIC CONDUIT (IMC) SHALL BE USED IN IN THE FILTER PIPE GALLERY TO MATCH EXISTING.
- 6. SEE DRAWING MO9 FOR TURBIDITY AND PARTICLE COUNTER INSTRUMENTATION RACK DETAIL.

### **KEY NOTES:**

- (A) INFLUENT SLUICE GATE SG-3081
- B DRAIN SLUICE GATE SG-308D
- (C) AIR SCOUR VALVE SIDE A BFV-308AA
- D BACKWASH VALVE SIDE A BFV-308WA
- (E) MASTER VALVE BFV-308M
- $\langle F \rangle$  EFFLUENT VALVE FCV-308E
- G RINSE VALVE BFV-308R
- H AIR SCOUR VALVE SIDE B BFV-308AB
- (I) BACKWASH VALVE SIDE B BFV-308WB
- J TURBIDITY METER, SIDE A AIT-308A
- (K) TURBIDITY METER, SIDE B AIT-308B
- (L) PARTICLE COUNTER AIT-308C
- M SIDE A LEVEL TRANSDUCER LE-308A
- $\langle N \rangle$  SIDE A LEVEL CONTROLLER LIT-308A
- (0) SIDE B LEVEL TRANSDUCER LE-308B
- (P) SIDE B LEVEL CONTROLLER LIT-308B
- $\mathbb{Q}$  EFFLUENT FLOW FIT-308
- R DIFFERENTIAL PRESSURE (HEAD LOSS) PDIT-308
- R FILTER CONTROL CONSOLE 7/8 (FCC 7/8) (EXISTING)
- $\langle S \rangle$  PANEL LF-4 (EXISTING)
- T EXISTING FILTER CONTROL CONSOLE. TO BE REMOVED.



GUSTA UTILITIES DEPARTMENT ND AVE WATER TREATMENT PL TER MODIFICATIONS - PHASE 2 PLAN ELECTRICAL  $\infty$ rer AU( HIGHLAI FIL FIET

Water Is Life AUGUSTA UTILITIES



FILE SEE LEFT VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING

DATE MARCH 2025 PROJ. 100339.11

E14